

Skeie | Artist™

TECHNICAL SPECIFICATION

skeie®

Skeie Seating AS,
Vestre Svanholmen 13
N-4313 Sandnes, Norway
—
E: seating@skeie.com
www.skeie.com

Reg.No. NO913369947MVA

DIMENSIONS

Low back, 920 mm: C/C 530, 550, 560 mm.
High back, 1095 mm: C/C 530, 550, 560 mm.

FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 60 x 40 x 3 mm.

Standard floor fixing: 240 x 156 x 8 mm steelbracket fixed to the rear of the tread.

Powder coated steel in standard RAL colors.

The chair is suitable for fixing in the riser, flat floor, and in straight or curved rows.

All fixings in chair are metal to metal and floor fixed for every other chair.

SEAT

Seatpad in cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 100 mm.

Smooth, quiet tip-up spring mechanism - N.T.I. approved according to ISO 7173, Level 5 (highest level).

Upholstery sewn to measurements and easily removable with zipper solution.

SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness 70 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Standard Figgjo armrest in molded laminated wood: thickness 20 mm, width 40 - 80 mm.

Alternative Soma armrest in molded laminated wood: thickness 20 mm, width 40 - 80 mm.

Fully upholstered armrest side panel fixed to steel frame also available.

OPTIONAL W/ WRITING TABLE

Foldable writing tablet in armrest, Notis A, 12 mm plywood w/ laminate top.

Top of armrest: 20 mm thick and 43 mm wide in beech or birch fixed to steeltube.

Armrest side panel is 6,5 mm plywood covered w/ fabric.

PS! Writing tablet in armrest increases the C/C with 10 mm.

ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Row and seat numbers are available.

Other qualities and measurements are available upon request.

PS! C/C 500, 520, 580, 600 mm with tall back - please ask for Symposium configuration.